

PURCHASING & PRODUCT SPECIFICATION INFORMATION

★NEW LIDS™ FULLY ENCLOSED SHELTER (FES)

WFI PART NUMBER

WFI-LIDS-FES

GSA PART NUMBER

SHIPPING INFORMATION

Shipping information can be requested by contacting Wel-Fab Inc. ® on our toll free number at 888-275-0881 or by e-mailing our Business Manager pielstone@wel-fab.com

PURCHASING INFORMATION

MAILING ADDRESS:

Wel-Fab, Inc.®
P.O. Box 86
Lumberton, NJ 08048

PHONE/FAX:

Phone: 888-275-0881 (Toll Free)
Fax: 609-267-6751

FAXED QUOTE REQUESTS:

609-267-6751
When faxing us your quote request please ensures your request is sent on agency letterhead with all customer contact information on it, to help us ensure a timely response to your quote request.

FOR ORDER CONFIRMATION:

For order confirmation, shipping information, contact Wel-Fab Inc. ® on our toll free number at 888-275-0881 or by e-mailing our Business Manager pielstone@wel-fab.com

TECHNICAL

INFORMATION/QUESTIONS:

Contact Rick Murray @
<mailto:rickmurray@wel-fab.com>



Wel-Fab, Inc. newly developed LIDS Fully Enclosed Shelter (FES) assembly was specifically engineered for today's quick response Military, Emergency Management, Emergency Medical, and Disaster Response Teams.

Our FES assembly provides a comfortable area where personnel can work or sleep safely within a fully enclosed tent structure. It can also serve as a central staging/collection point for incident responses or forward deployed command and control operating stations.

The LIDS FES consist of one lightweight inflatable shelter which is 10' x 10' x 8' in size, and has a fully enclosed canopy. All FES assemblies can be joined together end-to-end with other FES units using an interlocking Velcro connection ensuring a water-resistant seal between shelters. This shelter-to-shelter connection option is standard on all of our new LIDS FES units.

Our FES assemblies are completely enclosed and have an Environmental Control Unit (ECU) Heating/Cooling Integration Chute that allows heating and cooling units to be used to control the temperature within the shelter.

Tent shelter ends can be rolled up to allow shaded airflow through the shelter. This shelter significantly reduces exposure of personnel to high heat conditions accoicated from direct sunlight. It packs neatly into our weatherproof, lockable, harden and soft type LIDS shelter container capability.

The benefits of owning this ultimate Fully Enclosed Shelter assembly translates into unparalleled logistic improvements, including a smaller unit/team response footprint; reduced tent setup/breakdown times, and fastest relocation times during extremely austere and diverse emergency response conditions within all types of field operations.

★NEW LIDS™ FULLY ENCLOSED SHELTER

Configuration and Performance Data:

- **Rapid Deployment and Setup:**
 - Quickly Moved And Deployed In Minutes By 1-Person
 - Low Combined Tent Shelter And Container Weight: 154lbs
 - Complete Tent Shelter System Set-up in under 5 minutes
 - Each Tent shelter structure inflates in 120 seconds less
 - Simplified Training Requirements
 - Tent Shelter-To-Tent Shelter Complexing
- **Protective Shelter Canopy:**
 - Fully Enclosed Tent Shelter Canopy
 - Made from Tan Rip-Stop Nylon Material-70 Denier, 1.9oz
 - Weather Resistance And durable In Any Operating Environment
 - Environmental Control Unit (ECU) Heating/Cooling Integration Chute
 - Roll Up Canopy End Panels (Closed/Vented Tent Shelters)
 - Water Proof Shelter-to-Shelter Connection
 - Four Windows-With Covers
- **Shelter Floor Material:**
 - New extremely durable 15.0 oz./sq. yd. Berry Amendment Compliant
 - Floor Liner System Is Integrated With the Outer Canopy Fabric
 - RF Welded Floor Seams Provide Strong Waterproof Seals
 - More Durable Flooring Bottom-Abrasion Resistant
- **Multi Surface Setup/Anchoring Capabilities:**
 - **Soft Surfaces (Grass/Dirt):** Weight Bag Kit, Water Bags, and Spike Stakes
 - **Hard Surfaces (Concrete/Black Top):** Weight Bag Kit, Water Bags
- **Interior Lighting System:**
 - 2 Water Resistant, Tube Lights
- **Components:**
 - Weatherproof, Lockable, Hardden Tent Shelter Container
 - Optional Soft Pack Container Available
 - 110volt Blower/Vacuum Assembly
 - 50ft Electrical Cord
- **Industry Leading System Warranty:**
 - Initial 3 year warranty
 - Extendable up to 9 years with 3 year maintenance service contracts



CHEMICAL

BIOLOGICAL

RADIOLOGICAL

NUCLEAR

EXPLOSIVE

LIDS™ CBRNE

LIDS FULLY ENCLOSED SHELTER INFORMATION



LIDS™ Fully Enclosed Shelter (FES)		
LIDS™ Fully Enclosed Shelter (FES)	Quantity	Remarks
Shelter (10'X10') Assembly	1ea	
Tent Shelter Container Assembly, Pelican Case	1ea	
110volt Blower/Vacuum Assembly	1ea	
50ft Electrical Cord, Heavy Duty	1ea	
Ground Fault Interrupter (GFI) Plug	1ea	
Internal, Weather Proof Lighting	2ea	
Tent Shelter Staking System	1Kit	
Tent Shelter, Water Ballast Tubes	2ea	
Packing Strap	1ea	
Repair Kit	1ea	